




# MINILED XDH10

10.5 Watts / 1390 Lumens / 90+ CRI




10 Watt low glare LED downlight featuring a single COB LED design available in 2700K, 3000K, 4000K and 5000K colour temperature options in 90+ CRI or 2700K, 3000K and 4000K VIVID options. The Miniled range is supplied with remote driver.



System Power	11.7W	Cut-Out	92mm
LED Power	10.5W	Weight	345g
IP Rating	IP20		

	2700K	3000K	4000K	5000K	VIVID	2700K	3000K	4000K
COB Lumen Output	1300 lm	1335 lm	1390 lm	1410 lm	VIVID	1080 lm	1120 lm	1150 lm
Total Luminous Flux	640 lm	657 lm	684 lm	709 lm		531 lm	551 lm	566 lm

Efficacy	58.46 lm/W 4000K Narrow Beam	Lifetime	50,000hrs (L80)
Dimming	Leading + Trailing Edge		Optional: Dali 1-10v
Input Voltage	100V - 240V AC 50/60 Hz	Protection	Thermal and Short Circuit
		Power Factor	> 0.95



XDH103-NB-W

\* Optional



**TREND**  
LIGHT BY SOLID STATE

288 Coward Street, Mascot, NSW, 2020  
Ph: (02) 9669 8888 Fax: (02) 9669 8899 Email: sales@trendlighting.com.au