



Scan to explore
XMA10 online

Miniled XMA10

10W Recessed Square Downlight

Product Code	Colour Temperature	Colour Technology	Beam Angle	Trim Colour	Driver
XMA10	2.7 (2700K)	(CRI 90+ Standard)	NB (Narrow)	W (White)	LT (Leading & Trailing Edge)
	3 (3000K)	V (CRI 93+ VIVID)	MB (Medium)	B (Black)	DALI (DALI)
	3.5 (3500K)	R (CRI 97+ Standard)	WB (Wide)	S (Silver)	110V (1-10V)
	4 (4000K)				

Order Code **XMA104-WB-W-LT**



Product Features

- Single recessed LED downlight with square trim
- Also available in a twin configuration ([XMA210](#)) or as a row of three ([XMA310](#))
- Manufactured with an aluminium body and powder coat finish
- CRI 90+ available in 2700K, 3000K, 3500K and 4000K CCT options; CRI 93+ VIVID and CRI 97+ available in 2700K, 3000K and 4000K CCT options
- Supplied with a remote driver

Product Attributes




To configure this downlight, please visit
trendlighting.com.au/product/miniled-XMA10

Physical Characteristics

Trim Colour	White Black Silver
Dimensions (LxWxH)	100 x 100 x 105 mm
Spring Height	32 mm
Cutout	Circular 89 mm
Weight	394 g

Dimensions (mm)



 Cutout Ø89 mm

Technical Characteristics

Based on XMA104-WB-W-LT

LED Power	10.5W
LED Type	COB
Lumen Output	1450 lm
Luminous Flux	1019 lm
Efficacy	87.09 lm/W
Colour Temperature	2700K 3000K 3500K 4000K
Colour Technology	CRI 90+ CRI 93+ VIVID CRI 97+
Colour Deviation	SDCM ≤ 3
Lifetime	50,000 hours (L80)
Beam Angle	Narrow Medium Wide

System Power	11.7W Typical
Driver Model	Trend 150218-300 (L&T)
Input	180-265V AC 50/60 Hz
Output	30-42V DC 300mA
Power Factor	>0.93
Protection	OVP, OTP, OCP, SCP, OPP
Dimming	Leading & Trailing Edge DALI 1-10V

General Characteristics

Category	Downlights
Family	Miniled
Surface	Ceiling
Mounting	Recessed
Insulation Contact	Non-IC
Ingress Protection	IP20



Scan to explore
XMA10 online

Miniled XMA10

10W Recessed Square Downlight

Product Code	Colour Temperature	Colour Technology	Beam Angle	Trim Colour	Driver
XMA10	2.7 (2700K)	(CRI 90+ Standard)	NB (Narrow)	W (White)	LT (Leading & Trailing Edge)
	3 (3000K)	V (CRI 93+ VIVID)	MB (Medium)	B (Black)	DALI (DALI)
	3.5 (3500K)	R (CRI 97+ Standard)	WB (Wide)	S (Silver)	110V (1-10V)
	4 (4000K)				

Order Code **XMA104-WB-W-LT**

To configure this downlight, please visit
trendlighting.com.au/product/miniled-XMA10

Trim Colour



W
White Trim



B
Black Trim



S
Silver Trim