



Scan to explore
LST1 online

Slot LST1

2W Recessed Tiny Square Downlight

Product Code	Colour Temperature	Colour Technology	Beam Angle	Trim Colour
LST1	3 (3000K)	(CRI 90+ Standard)	WB (Wide)	W (White)
	4 (4000K)			B (Black)

Order Code **LST14-WB-W**



Product Features

- Recessed miniature square LED linear downlight crafted with aesthetics and visual comfort in mind
- Equipped with a single deep set light optic specifically designed for glare control, minimising the presence of the luminaire within the field of vision
- CRI 90+ available in 3000K and 4000K CCT options
- Supplied with a remote driver and 240V flex and plug

Product Attributes




To configure this downlight, please visit
trendlighting.com.au/product/slot-LST1

Physical Characteristics

Trim Colour	White Black
Dimensions (LxWxH)	44 x 44 x 42 mm
Cutout	Square 36 x 36 mm
Weight	110 g

Dimensions (mm)




Technical Characteristics

Based on LST14-WB-W

LED Power	2W
LED Type	COB
Lumen Output	247 lm
Luminous Flux	200 lm
Efficacy	60.61 lm/W
Colour Temperature	3000K 4000K
Colour Technology	CRI 90+
Colour Deviation	SDCM ≤ 3
Lifetime	50,000 hours (L70)
Beam Angle	Wide
System Power	3.3W Typical

General Characteristics

Category	Downlights, Linears & Battens
Family	Slot
Surface	Ceiling
Mounting	Recessed
Insulation Contact	Non-IC
Ingress Protection	IP20



Scan to explore
[LST1 online](#)

Slot LST1


2W Recessed Tiny Square Downlight

Product Code	Colour Temperature	Colour Technology	Beam Angle	Trim Colour
LST1	3 (3000K)	(CRI 90+ Standard)	WB (Wide)	W (White)
	4 (4000K)			B (Black)


Order Code **LST14-WB-W**

To configure this downlight, please visit
trendlighting.com.au/product/slot-LST1

Trim Colour



W
White Trim



B
Black Trim