

## Auro TS1525

Switchable Wattage Tri-colour Track Spot

Track mounted LED spotlight designed with slim profile and manufactured with an aluminium powder coated body. An ideal lighting solution for architectural applications.

Equipped with technology that allows users to alternate between three wattage settings and colour temperature options (3000K, 4000K, 5000K) offering versatility and customisation. Supplied with an integral flicker free driver.







Order Co	Driver	Trim Colour	ССТ	Product
TS1525-TRI-W-	Non-dim	White Trim	Tri-colour	TS1525
TS1525-TRI-B-		Black Trim		

## Specifications

opeenieunenie	
Trim Colour Options	White   Black
Dimensions	Ø85 x 270 (H) mm
Tilt Angle	90°
Rotation	350°
Weight	925 g
LED Power	Switchable 15W, 20W, 25W
LED Type	СОВ
Lumen Output	1600 lm, 2050 lm, 2500 lm
Efficacy	101 lm/W, 98 lm/W, 97 lm/W
CCT Technology	Tri-colour Switchable
Colour Temperature	3000K, 4000K, 5000K
Colour Rendering	CRI 90+
Lifetime	50,000 hours
Beam Angle	Wide 60°
System Power	15.8W, 20.8W, 25.8W Typical
Input	220-240V AC 50/60 Hz
Power Factor	>0.90
Dimming	Non-dimmable
Driver Type	Integral, Flicker Free
Connection Type	Track Mounted
Ingress Protection	IP20



Diameter 85 mm



Diameter 85 mm





Trend For Trade. Made For Trade.