



Scan to explore
XDF15 online

Midiled XDF15

15W IP65 Rated Recessed Downlight

Product Code	Colour Temperature	Colour Technology	Beam Angle	Trim Colour	Insert Colour	Driver
XDF15	2.7 (2700K)	(CRI 90+ Standard)	NB (Narrow)	W (White)	WI (White)	LT (Leading & Trailing Edge)
	3 (3000K)	V (CRI 93+ VIVID)	MB (Medium)	B (Black)	BI (Black)	DALI (DALI)
	3.5 (3500K)	R (CRI 97+ Standard)	WB (Wide)	S (Silver)	SI (Silver)	110V (1-10V)
	4 (4000K)				GI (Gold)	

Order Code **XDF154-WB-W-WI-LT**



To configure this downlight, please visit
trendlighting.com.au/product/midiled-XDF15

Product Features

- Recessed LED downlight with IP65 rating characterised by its quality, light efficiency and performance
- Manufactured with an aluminium body and powder coat finish
- Large pin fin heatsink for optimal thermal management
- A wide choice of power options and sizes available (XDF10, XDF25, XDF35 and XDF55)
- CRI 90+ available in 2700K, 3000K, 3500K and 4000K CCT options; CRI 93+ VIVID and CRI 97+ available in 2700K, 3000K and 4000K CCT options
- Supplied with a remote driver


Product Attributes



Physical Characteristics

Trim Colour	White Black Silver
Insert Colour	White Black Silver Gold
Dimensions	Ø150 x 125 (H) mm
Spring Height	32 mm
Cutout	Circular 120 mm
Weight	490 g

Dimensions (mm)



Technical Characteristics

Based on XDF154-WB-W-WI-LT

LED Power	15W
LED Type	COB
Lumen Output	2004 lm
Luminous Flux	1613 lm
Efficacy	88.63 lm/W
Colour Temperature	2700K 3000K 3500K 4000K
Colour Technology	CRI 90+ CRI 93+ VIVID CRI 97+
Colour Deviation	SDCM ≤ 2
Lifetime	50,000 hours (L80)
Beam Angle	Narrow Medium Wide

System Power	18.2W Typical
Driver Model	Trend 150016-420 (L&T)
Input	180-265V AC 50/60 Hz
Output	30-40V DC 420mA
Power Factor	>0.90
Protection	OVP, OTP, OCP, SCP, OPP
Dimming	Leading & Trailing Edge DALI 1-10V

General Characteristics

Category	Downlights
Family	Midiled
Surface	Ceiling
Mounting	Recessed
Insulation Contact	Non-IC
Ingress Protection	IP65



Scan to explore
XDF15 online

Midiled XDF15

15W IP65 Rated Recessed Downlight

Product Code	Colour Temperature	Colour Technology	Beam Angle	Trim Colour	Insert Colour	Driver
XDF15	2.7 (2700K)	(CRI 90+ Standard)	NB (Narrow)	W (White)	WI (White)	LT (Leading & Trailing Edge)
	3 (3000K)	V (CRI 93+ VIVID)	MB (Medium)	B (Black)	BI (Black)	DALI (DALI)
	3.5 (3500K)	R (CRI 97+ Standard)	WB (Wide)	S (Silver)	SI (Silver)	110V (1-10V)
	4 (4000K)				GI (Gold)	

Order Code **XDF154-WB-W-WI-LT**

To configure this downlight, please visit
trendlighting.com.au/product/midiled-XDF15

Trim Colour



W
White Trim



B
Black Trim



S
Silver Trim

Insert Colour




WI
White Insert



BI
Black Insert



SI
Silver Insert



GI
Gold Insert