

Midiled XMC125

25W Recessed Adjustable Square Downlight



Scan to explore XMC125 online

Product Code	Co	lour Temperature	Colour Technology	Beam Angle	Trim Colour	Driv	er
XMC125	3 4	(3000K) (4000K)	(CRI 90+ Standard)	MB (Medium)	W (White) B (Black)	LT	(Non-dimmable) (Leading & Trailing Edge) (DALI)

Order Code XMC1254-MB-B-ND




To configure this downlight, please visit trendlighting.com.au/product/midiled-XMC125

Physical Characteristics

Trim Colour	White Black		
Tilt Angle	35° x 35°		
Dimensions (LxWxH)	175 x 175 x 110 mm		
Spring Height	35 mm		
Cutout	Square 160 x 160 mm		
Weight	1350 g		

Dimensions (mm)









Product Features

- Single recessed adjustable LED downlight in square housing
- Also available in a twin configuration (XMC225) or as a row of three (XMC325)
- CRI 90+ available in 3000K and 4000K CCT options
- Anodised black heatsink for effective thermal management ensuring high output and long lifespan
- Supplied with a remote driver

Product Attributes











Technical Characteristics	Based on XMC1254-MB-B-ND			
LED Power	25W			
LED Type	COB			
Lumen Output	2955 lm			
Luminous Flux	2500 lm			
Efficacy	94.70 lm/W			
Colour Temperature	3000K 4000K			
Colour Technology	CRI 90+			
Colour Deviation	SDCM ≤ 3			
Lifetime	50,000 hours (L80)			
Beam Angle	Medium			
System Power	26.4W Typical			
Driver Model	Trend 150020-700 (Non-dim)			
Input	180-265V AC 50/60 Hz			
Output	30-40V DC 700mA			
Power Factor	>0.90			
Protection	OVP, OTP, OCP, SCP, OPP			
Dimming	Non-dimmable			
	Leading & Trailing Edge DALI			

General Characteristics

Category	Downlights
Family	Midiled
Surface	Ceiling
Mounting	Recessed
Insulation Contact	Non-IC
Ingress Protection	IP20



Midiled XMC125

25W Recessed Adjustable Square Downlight



Scan to explore XMC125 online

Product Code	Colour Temperature	Colour Technology	Beam Angle	Trim Colour	Driver
XMC125	3 (3000K) 4 (4000K)	(CRI 90+ Standard)	MB (Medium)	W (White) B (Black)	ND (Non-dimmable) LT (Leading & Trailing Edge) DALI (DALI)

Order Code XMC1254-MB-B-ND

To configure this downlight, please visit

trendlighting.com.au/product/midiled-XMC125

Trim Colour





White Trim

Black Trim