



Scan to explore  
XRA20 online

# Midiled XRA20

18W Recessed Adjustable Downlight

Product Code	Colour Temperature	Colour Technology	Beam Angle	Trim Colour	Insert Colour	Driver
XRA20	3 (3000K)	(CRI 90+ Standard)	MB (Medium)	W (White)	WI (White)	LT (Leading & Trailing Edge)
	4 (4000K)			B (Black)	BI (Black) SI (Silver) GI (Gold)	

Order Code **XRA204-MB-W-WI-LT**



To configure this downlight, please visit  
[trendlighting.com.au/product/midiled-XRA20](http://trendlighting.com.au/product/midiled-XRA20)

## Product Features

- Recessed adjustable LED downlight with configurable inserts, providing versatility in lighting and aesthetic design
- Featured with 355° rotation and 45° tilting capabilities, allowing for directional adjustment in a variety of lighting applications
- CRI 90+ available in 3000K and 4000K CCT options
- Supplied with a remote driver


## Product Attributes



## Physical Characteristics

Trim Colour	White   Black
Insert Colour	White   Black   Silver   Gold
Tilt Angle	45°
Rotation	355°
Dimensions	Ø135 x 170 (H) mm
Spring Height	24 mm
Cutout	Circular 122 mm
Weight	890 g

## Dimensions (mm)



## Technical Characteristics

Based on XRA204-MB-W-WI-LT

LED Power	18W
LED Type	COB
Lumen Output	2266 lm
Luminous Flux	1248 lm
Efficacy	62.40 lm/W
Colour Temperature	3000K   4000K
Colour Technology	CRI 90+
Colour Deviation	SDCM ≤ 2
Lifetime	50,000 hours (L80)
Beam Angle	Medium

System Power	20W Typical
Driver Model	Trend 150016-420 (L&T)
Input	180-265V AC 50/60 Hz
Output	30-40V DC 420mA
Power Factor	>0.90
Protection	OVP, OTP, OCP, SCP, OPP
Dimming	Leading & Trailing Edge   DALI   1-10V

## General Characteristics

Category	Downlights
Family	Midiled
Surface	Ceiling
Mounting	Recessed
Insulation Contact	Non-IC
Ingress Protection	IP20



Scan to explore  
XRA20 online

# Midiled XRA20

18W Recessed Adjustable Downlight

Product Code	Colour Temperature	Colour Technology	Beam Angle	Trim Colour	Insert Colour	Driver
XRA20	3 (3000K)	(CRI 90+ Standard)	MB (Medium)	W (White) B (Black)	WI (White)	LT (Leading & Trailing Edge) DALI (DALI) 110V (1-10V)
	4 (4000K)				BI (Black) SI (Silver) GI (Gold)	

Order Code **XRA204-MB-W-WI-LT**

To configure this downlight, please visit  
[trendlighting.com.au/product/midiled-XRA20](http://trendlighting.com.au/product/midiled-XRA20)

## Trim Colour



W  
**White Trim**



B  
**Black Trim**

## Insert Colour



WI  
**White Insert**



BI  
**Black Insert**



SI  
**Silver Insert**



GI  
**Gold Insert**