

Multiled DTL10

10 Watt Deep Recessed Tricolour Downlight

Compact deep recessed fixed SMD LED downlight with a slim design and opal polycarbonate diffuser for uniform lighting distribution. Aluminium housing provides excellent thermal management for exceptional heat dissipation. An ideal lighting solution for general lighting applications.

Featuring colour switchable technology that enables users to switch between 3 colour temperature options - 3000K (warm white), 4000K (cool white) and 5700K (daylight). Supplied with a remote flicker free Leading & Trailing Egde dimmable driver.







Product	сст	Trim Colour	Driver	Order Codes
DTL10	Tricolour	White Trim	Leading & Trailing Edge	DTL10-TRI-W-LT
		Black Trim		DTL10-TRI-B-LT

Specifications

opecifications		
Trim Colour Options	White Black	
Cutout	Ø90-95 mm	
Dimensions	Ø110 x 52 (H) mm	
Weight	260 g	
LED Power	10W	
LED Type	SMD	
Lumen Output	990 lm	
CCT Technology	Tri-colour Selectable	
Colour Temperature (CCT)	3000K, 4000K, 5700K	
Colour Rendering	CRI 85+	
Lifetime	50,000 hours (L70)	
Beam Angle	Wide 90°	
System Power	9.5W Typical	
Efficacy	Up to 104 lm/W	
Input	200-240V AC 50 Hz	
Power Factor	>0.95	
Dimming	Leading & Trailing Edge	
Driver Type	Remote, Flicker Free	
Connection Type	Flex and Plug	
Ingress Protection	IP54	
Insulation Rating	IC-4 AS/NZS 60598.2.2	
IEC Protection	Class II	
Warranty	3 Years	





Overall Diameter 110 mm







Trend For Trade. Made For Trade.