

Platinum P12C

12W Recessed Premium Downlight



P12C online

* Optional accessories

Product Code	Tri	m Colour	Colour Temperature	Colour Technology	Beam Angle		Accessories *	Driver	
P12C	W B	(White) (Black)	927 (2700K) 930 (3000K) 935 (3500K) 940 (4000K)	(CRI 94+ Standard) S (CRI 98+ Optisolis)	20D 38D 60D	(Narrow) (Medium) (Wide)	SDR (Specular Dark Reflector)	LT DALI	(Leading & Trailing Edge) (DALI)

Order Code P12CW-940-60D-LT




To configure this downlight, please visit trendlighting.com.au/product/platinum-P12C

Physical Characteristics

Trim Colour	White Black			
Tilt Angle	30°			
Dimensions	Ø105 x 75 (H) mm			
Spring Height	20 mm			
Cutout	Circular 92 mm			
Weight	315 g			

Dimensions (mm)



Cutout Ø92 mm

Product Features

- Recessed premium adjustable LED downlight characterised by its versatility and superior colour rendering
- Manufactured with an aluminium body and powder coat finish
- Injection moulded twice vacuum metalised reflector for high reflectivity and uniform beam distribution
- Can be specified with specular dark reflector
- CRI 94+ and CRI 98+ Optisolis available in 2700K, 3000K, 3500K and 4000K CCT options
- · Supplied with a remote driver

Product Attributes



Technical Characteristics	Based on P12CW-940-60D-L				
LED Power	10W				
LED Type	COB				
Lumen Output	1350 lm				
Luminous Flux	1213 lm				
Efficacy	101.93 lm/W				
Colour Temperature	2700K 3000K 3500K 4000K				
Colour Technology	CRI 94+ CRI 98+ Optisolis				
Colour Deviation	$SDCM \le 2$				
Lifetime	60,000 hours (L80 B10)				
Beam Angle	Narrow Medium Wide				
System Power	11.9W Typical				
Driver Model	Trend 150218-300 (L&T) Black				
Input	180-265V AC 50/60 Hz				
Output	30-42V DC 300mA				
Power Factor	>0.93				
Protection	OVP, OTP, OCP, SCP, OPP				
Dimming	Leading & Trailing Edge DALI				

General Characteristics

Category	Downlights
Family	Platinum
Surface	Ceiling
Mounting	Recessed
Insulation Contact	CA90
Ingress Protection	IP20



Platinum P12C

12W Recessed Premium Downlight



P12C online

Product Code	Tri	m Colour	Colour Temperature	Colour Technology	Beam Angle		Accessories *	Driver	
P12C	W B	(White) (Black)	927 (2700K) 930 (3000K) 935 (3500K) 940 (4000K)	(CRI 94+ Standard) S (CRI 98+ Optisolis)	20D 38D 60D	(Narrow) (Medium) (Wide)	SDR (Specular Dark Reflector)	LT DALI	(Leading & Trailing Edge) (DALI)

Order Code P12CW-940-60D-LT

* Optional accessories

To configure this downlight, please visit

trendlighting.com.au/product/platinum-P12C


Trim Colour





W White Trim B Black Trim

Accessories *



SDR Specular Dark Reflector