

# **Platinum P12G**

#### 12W Recessed Premium Downlight



\* Optional accessories

Colour Temperature Product Code Trim Colour **Colour Technology** Beam Angle Accessories \* Driver P12G W (White) 927 (2700K) (CRI 94+ Standard) 20D (Narrow) SDR (Specular Dark Reflector) LT (Leading & Trailing Edge) (Medium) DALI (DALI) 930 (3000K) S (CRI 98+ Optisolis) 38D В (Black) 935 (3500K) 60D (Wide) 940 (4000K)

Order Code P12GW-940-60D-LT




To configure this downlight, please visit trendlighting.com.au/product/platinum-P12G

#### **Physical Characteristics**

Trim Colour	White   Black
Tilt Angle	30°
Dimensions	Ø105 x 90 (H) mm
Spring Height	20 mm
Cutout	Circular 92 mm
Weight	315 g

#### **Dimensions (mm)**



Cutout Ø92 mm

# Ø105



#### **Product Features**

- Recessed premium adjustable LED downlight characterised by its curved appearance and impeccable light quality
- Manufactured with an aluminium body and powder coat finish
- Injection moulded twice vacuum metalised reflector for high reflectivity and uniform beam distribution
- Can be specified with specular dark reflector
- CRI 94+ and CRI 98+ Optisolis available in 2700K, 3000K, 3500K and 4000K CCT options
- · Supplied with a remote driver

#### **Product Attributes**



Technical Characteristics	Based on P12GW-940-60D-LT
LED Power	10W
LED Type	COB
Lumen Output	1350 lm
Luminous Flux	1098 lm
Efficacy	92.27 lm/W
Colour Temperature	2700K   3000K   3500K   <b>4000K</b>
Colour Technology	CRI 94+   CRI 98+ Optisolis
Colour Deviation	SDCM ≤ 2
Lifetime	60,000 hours (L80 B10)
Beam Angle	Narrow   Medium   Wide
System Power	11.9W Typical
Driver Model	Trend 150218-300 (L&T) Black
Input	180-265V AC 50/60 Hz
Output	30-42V DC 300mA
Power Factor	>0.93
Protection	OVP, OTP, OCP, SCP, OPP
Dimming	Leading & Trailing Edge   DALI

## **General Characteristics**

Category	Downlights	
Family	Platinum	
Surface	Ceiling	
Mounting	Recessed	
Insulation Contact	CA90	
Ingress Protection	IP20	



# Platinum P12G

12W Recessed Premium Downlight



Product Code Trim Colour **Colour Temperature** Colour Technology Beam Angle Accessories \* Driver P12G 927 (2700K) (CRI 94+ Standard) SDR (Specular Dark Reflector) (Leading & Trailing Edge) W (White) 20D (Narrow) LT 38D (Medium) DALI (DALI) 930 (3000K) S (CRI 98+ Optisolis) В (Black) 935 (3500K) 60D (Wide) 940 (4000K)

Order Code P12GW-940-60D-LT

\* Optional accessories

To configure this downlight, please visit

trendlighting.com.au/product/platinum-P12G


## Trim Colour





W White Trim B Black Trim

## Accessories \*



SDR Specular Dark Reflector