

Platinum P12K

12W Recessed Premium Downlight



Scan to explore P12K online

| Product Code | Tri | m Colour | Colour Temperature | Colour Technology | Beam Ang | e Accessories * | Driv | Driver | |
|--------------|--------|--------------------|---|---|----------------------------------|-----------------|------|----------------------------------|--|
| P12K | W B | (White) (Black) | 927 (2700K) 930 (3000K) 935 (3500K) 940 (4000K) | (CRI 94+ Standard) S (CRI 98+ Optisolis) | 20D (Nam 38D (Med 60D (Wid | ium) | | (Leading & Trailing Edge) (DALI) | |

Order Code P12KW-940-60D-LT * Optional accessories




To configure this downlight, please visit trendlighting.com.au/product/platinum-P12K

Physical Characteristics

| Trim Colour | White Black |
|---------------|-------------------|
| Dimensions | Ø112 x 87 (H) mm |
| Spring Height | 20 mm |
| Cutout | Circular 76-92 mm |
| Weight | 315 g |

Dimensions (mm)

Cutout Ø76-92 mm



Product Features

- Recessed premium LED downlight, designed to visually integrate into the ceiling while providing low glare and high output
- Manufactured with an aluminium body and powder coat finish
- Injection moulded twice vacuum metalised reflector for high reflectivity and uniform beam distribution
- Can be specified with specular dark reflector
- CRI 94+ and CRI 98+ Optisolis available in 2700K, 3000K, 3500K and 4000K CCT options
- Supplied with a remote driver

Product Attributes











| Technical Characteristics | Based on P12KW-940-60D-LT |
|---------------------------|--------------------------------------|
| LED Power | 10W |
| LED Type | COB |
| Lumen Output | 1350 lm |
| Luminous Flux | 1213 lm |
| Efficacy | 101.93 lm/W |
| Colour Temperature | 2700K 3000K 3500K 4000K |
| Colour Technology | CRI 94+ CRI 98+ Optisolis |
| Colour Deviation | SDCM ≤ 2 |
| Lifetime | 60,000 hours (L80 B10) |
| Beam Angle | Narrow Medium Wide |
| System Power | 11.9W Typical |
| Driver Model | Trend 150218-300 (L&T) Black |
| Input | 180-265V AC 50/60 Hz |
| Output | 30-42V DC 300mA |
| Power Factor | >0.93 |
| Protection | OVP, OTP, OCP, SCP, OPP |
| Dimming | Leading & Trailing Edge DALI |

General Characteristics

| Category | Downlights | | |
|--------------------|------------|--|--|
| Family | Platinum | | |
| Surface | Ceiling | | |
| Mounting | Recessed | | |
| Insulation Contact | CA90 | | |
| Ingress Protection | IP44 | | |



Platinum P12K



12W Recessed Premium Downlight

| Product Code | Trim Colour | | Colour Temperature | Colour Technology | Beam Angle | | Accessories * | Driver | |
|--------------|-------------|--------------------|--|---|-------------------|--------------------------------|-------------------------------|-------------------|----------------------------------|
| P12K | W B | (White) (Black) | 927 (2700K) 930 (3000K) 935 (3500K) 940 (4000K) | (CRI 94+ Standard) S (CRI 98+ Optisolis) | 20D 38D 60D | (Narrow) (Medium) (Wide) | SDR (Specular Dark Reflector) | LT DALI | (Leading & Trailing Edge) (DALI) |


Order Code P12KW-940-60D-LT

* Optional accessories

To configure this downlight, please visit

trendlighting.com.au/product/platinum-P12K

Trim Colour






White Trim

Black Trim

Accessories *



SDR

Specular Dark Reflector